

K-EASE MEDALLION INSTALLATION

The K-ease medallion will accommodate light fixture canopies up to 5 ½ inches in diameter

**Please Read
And Follow All
Installation
Instructions
Carefully**




Figure 1




Figure 2

1. Pre-Installation preparation

- Pre-paint the medallion base and K-ease keystones before installation. (allow to dry) The medallion is a pre-primed, paint-ready surface.

2. Installation of the base

- You may apply a small bead of caulk to the back side of the medallion to ensure a tight seamless fit against the ceiling (this is recommended for sprayed “popcorn” ceilings)
- Place the first half of the medallion base around the canopy.
- Attach the half of the base to the ceiling by inserting drywall screws into the part of the base to be covered by the keystones. Screws should be approximately 1” from the outer rim of the medallion edge.
- Repeat the previous two steps for the other medallion base half.

Installation of the keystones

- Attach the first keystone to the base with a flathead screw (paying careful attention to line up the outer edge of the keystone with the outer edge of the medallion base.) The screw head should be even with or counter sunk into the base.
- Cover the screw heads with caulk or putty. Lightly sand to a smooth finish, and touch up these areas with paint for a finished look.
- Repeat these two steps with the other keystones.

Materials Needed:

- Ladder
- Screws
- Caulk
- Pencil
- Paint